SC 144 (1999) (Rev,1 Nov.1999) (Rev.2 Sept 2012) (<u>Rev.3</u> <u>Oct 2017</u>)

Periodic Servicing of Launching Appliances and on-load Releasing Gear

Maintenance, Thorough Examination, Operational Testing, Overhaul and Repair of Lifeboats, Rescue Boats and Fast Rescue Boats, Launching Appliances and Release Gear

SOLAS Regulation III/20.11 reads:

11.1. Launching appliances shall be:

.3. <u>.2</u> upon completion of the examination referred to in <u>.2</u> <u>paragraph 11.1.1</u>, subjected to a dynamic test of the winch brake at maximum lowering speed. The load to be applied shall be the mass of the survival craft or rescue boat without persons on board, except that, at intervals not exceeding <u>of at least once every</u> five years, the test shall be carried out with a proof load equal to 1.1 times the weight of the survival craft or rescue boat and its full complement of persons and equipment.

11.2. Lifeboat or <u>and</u> rescue on-load boat release gear, including <u>fast rescue boat release</u> <u>gear</u> and free-fall lifeboat release systems, shall be:

<u>.3. .2</u> in case of on-load release gear, operationally tested under a load of 1.1 times the total mass of the boat when loaded with its full complement of persons and equipment whenever the release gear is overhauled. Such over-hauling overhauling and operational test shall be carried out at least once every five years.

<u>.3</u> notwithstanding paragraph 11.2.2, the operational testing of free-fall lifeboat release systems shall be performed either by free fall launch with only the operating crew on board or by a test without launching the lifeboat carried out based on requirements for maintenance, thorough examination, operational testing, overhaul and repair.

11.3. Davit-launched liferaft automatic release hooks shall be:

<u>.3. .2</u> operationally tested under a load of 1.1 times the total mass of the liferaft when loaded with its full complement of persons and equipment whenever the automatic release hook is overhauled. Such over-hauling <u>overhauling</u> and <u>operational</u> test shall be carried out at least once every five years.

Note:

- 1. This Unified Interpretation is to be uniformly implemented by all Members and associates from 1 July 1999, unless otherwise instructed by a Flag State.
- 2. Changes introduced in Rev.1 are to be applied from 1 July 1999.
- 3. Changes introduced in Rev.2 are to be applied from 1 January 2013.
- 4. Changes introduced in Rev.3 are to be applied from 1 January 2020.

Interpretation

SC

144

(cont)

The thorough examinations/overhauls and <u>operational</u> tests in five year intervals, carried out <u>at intervals of at least once every five years,</u> shall be done in the presence of a surveyor.

End of Document